

NATIONAL CHEMICAL LABORATORIES, INC.

narcotic effects

SAFETY DATA SHEET

Section 1 - Identification

Product Identifier 20X Glass and Window Cleaner Concentrate

Other means of identification 1325

Recommended use Glass & Window Cleaner

Recommended restrictions For commercial and industrial use only. This product is intended to be diluted prior to use.

Manufacturer / Importer / Supplier / Distributor Information

Company NameNational Chemical Laboratories of PA, Inc.Address401 N. 10th Street - Philadelphia, PA 19123

Telephone 1 (215) 922-1200
Supplier Email info@nclonline.com
Contact CHEM-TEL
Emergency Phone 1 (800) 255-3924

Section 2 - Hazard(s) Identification

SDS Hazards and Warnings are based on the undiluted product. Refer to diluted SDS for Ready-To-Use Hazards and Warnings.

ClassificationCategoryFlammable Liquids3Serious eye damage/eye irritation2Skin corrosion/irritation2

Specific target organ toxicity, single exposure 3

OSHA defined hazards

Label Elements

Physical Hazards

Health Hazards

Hazard Symbol



Not Classified.



Signal Word Danger

Hazard Statement Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container

and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only

outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person

to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash

before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Section 3 - Composition/Information on ingredients

Mixture

 Hazardous Components
 Ingredient Name
 CAS #
 %

 2-Propanol
 67-63-0
 20 - 25

 2-Butoxyethanol
 111-76-2
 10 - 15

 2-Amino Ethanol
 141-43-5
 1 - 5

Composition Comments Components not listed are either non-hazardous or are below reportable limits.

Section 4 - First-aid Measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician

if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.

Most Important symptoms /effects, acute and delayed May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging,

tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep

victim under observation. Symptoms may be delayed.

General Information Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take

precautions to protect themselves. Wash contaminated clothing before reuse.

Section 5 - Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back.

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment /instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

General fire hazards Highly flammable liquid and vapor.

Specific Methods Use standard firefighting procedures and consider the hazards of other involved materials.

Section 6 - Accidental release measures

Personal precautions, protective equipment and emergency procedures.

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This

product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Section 7 - Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage. including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the

SDS).

Section 8 - Exposure control/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components Value Type 6 mg/m³, 3 ppm 2-Amino Ethanol (CAS 141-43-5) **TWA** 240 mg/m³, 50 ppm 2-Butoxyethanol (CAS 111-76-2) TWA 2-Propanol (CAS 67-63-0) TWA 980 mg/m³, 400ppm

US. ACGIH Threshold Limit Values

Component Type Value Form

Form

2-Propanol (CAS 67-63-0)	TWA	200 ppm
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
2-Amino Ethanol (CAS 141-43-5)	STEL	6 ppm
2-Amino Ethanol (CAS 141-43-5)	TWA	3 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components Type Value

2-Amino Ethanol (CAS 141-43-5) STFL 15 mg/m3, 6 ppm 2-Amino Ethanol (CAS 141-43-5) TWA 8 mg/m^3 , 3 ppm2-Butoxyethanol (CAS 111-76-2) TWA 24 mg/m³, 5 ppm

2-Propanol (CAS 67-63-0) 2000 ppm **IDLH**

2-Propanol (CAS 67-63-0) STEL 1225 mg/m³, 500 ppm 2-Propanol (CAS 67-63-0) Τ\Λ/Δ 980 mg/m³, 400 ppm

US. ACGIH. BEIs. Biological Exposure Indices

Sampling Time Components Value Determinate Specimen Butoxyacetic acid (BAA), 2-Propanol (CAS 67-63-0) 200 mg/g Creatinine in urine

with hydrolysis

2-Propanol (CAS 67-63-0) 40 mg/l Acetone Urine 2-Butoxyethanol (CAS 111-76-2) Butoxyacetic acid (BAA), Creatinine in urine 200 mg/g

with hydrolysis

* - For sampling details, please see the source document.

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components Exposure

Can be absorbed though the skin. 2-Butoxyethanol (CAS 111-76-2)

US.Minnesota Hazardous Substances List (Minn. Rules 5206.0400).

Components Exposure

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

US.NIOSH: Pocket Guide to Chemical Hazards

Component Exposure

2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.100)

Components Exposure

2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.OSHA Table Z-1-A (29 CFR 1910.100)

Components Exposure

2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin. US.Rhode Island Hazardous Substances Right-to-Know Act (R.I. Gen. Laws Section 28-21-1 et. seq.)

Components Exposure

2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

US.Tennesee. OELs Occupational Exposure Limkits, Table Z1A

Components Exposure

2-Butoxyethanol (CAS 111-76-2) Can be absorbed though the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Wear protective gloves.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material

considerations and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants

Section 9 - Physical and chemical properties

Appearance

Physical state Liquid.

Form Dark opaque, thin liquid.

Color Dark Blue.
Odor Alcohol.
Odor threshold Not available.
pH 11.5

Melting point/freezing point Not relevant.

Initial boinging point and 177 - 212°F (80.6 - 100°C)

boiling range

Flash point 76°F (24.4°C) Tag Closed Cup

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Flammability limit - lower (%) Not available. Flammability limit - upper (%) Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Not available. Vapor density Not available. Relative density 0.94 ± 0.01 Relative density temperature 75 °F (23.9 °C) Solubilities (water) Completely soluable.

Partition Coefficient noctanol/water

Not available

Auto-ignition temperatureNot AvailableDecomposition temperatureNot AvailableViscosity<10 cSt</th>Viscosity Temperature75 °F (23.9 °C)

Section 10 - Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possiblity of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to Avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with

incompatible materials.

Incompatible materialsStrong oxidizing agents. Isocyanates. Chlorine.Hazardous DecompositionNo hazardous decomposition products are known.

Products

Section 11 - Toxicological information

Information on likely routes of exposure

Ingestion May be harmful if swallowed.

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Level

Skin contact Causes skin irritation.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Components

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging,

Code

Species

tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Type

Information on toxicological effects.

Acute toxicity Narcotic effects.

2-Amino Ethanol (CAS 141-43-5)	Acute	Dermal	LD50	Rabbit	1025 mg/kg
	Acute	Oral	LD50	Rat	1715 mg/kg
2-Butoxyethanol (CAS 111-76-2)	Acute	Dermal	LD50	Rabbit	400 mg/kg
	Acute	Inhalation	LC50	Mouse	700 ppm, 7 hours
	Acute	Inhalation	LC50	Rat	450 mg/l, 4 hrs
	Acute	Oral	LD50	Guinea pig	1.2 g/kg
	Acute	Oral	LD50	Mouse	1519 mg/kg
	Acute	Oral	LD50	Rabbit	0.32 g/kg
	Acute	Oral	LD50	Rat	560 mg/kg

Skin corrosion/irritation Causes skin irritation.

Results

Serious eye damage/ eye

irritation

Causes serious eye irritation.

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

3

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Component

Result

2-Butoxyethanol (CAS 111-76-2)

Not classifiable as to carcinogenicity to humans.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

May cause drowsiness and dizziness.

single exposure

Specific target organ toxicity -

Not classified.

repeated exposure Aspiration hazard

Not an aspiration hazard.

May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

Chronic effects

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Section 12 - Ecological Information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Component(s)

2-Amino Ethanol, 141-43-5

Aquatic

Level Type Code Species **Test Results** EC50 Selenastrum capricornutum (new name 2.5 mg/l, 48 hours Acute Algae

FC50

LC50

LC50

Pseudokirchnerella subca

Daphnia magna 65 mg/l, 48 hours Goldfish (Carassius auratus) 170 mg/l, 96 hours Cyprinus carpio 349 mg/l, 96 hours

Persistence and degradability

The product is expected to be biodegradable.

Bioaccumulative potential Partition coefficient n-octanol / water log (Kow)

Crustacea

Fish

Fish

Components Results 2-Propanol (CAS 67-63-0) 0.05 2-Butoxyethanol (CAS 111-76-2) 0.83 2-Amino Ethanol (CAS 141-43-5) -1.31

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine

disruption, global warming potential) are expected from this component.

Section 13 - Disposal considerations

Disposal instructions Dispose in accordance with applicable federal, state, and local regulations.

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code Waste codes should be assigned by the user based on the application for which the product was used.

Waste from residues / unused

Dispose in accordance with all applicable regulations.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Section 14 - Transport information

DOT

products

UN number

Proper shipping name ALCOHOLS SOLUTION, N.O.S. (2-PROPANOL)

Transport hazard class(es) 3 Subsidary class(es) Packing group

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Labels required

B1, IB3, T4, TP1, TP29

Special provisions

Packaging exemption 150

Packaging non bulk 203 Packaging bulk 242

IATA

UN number UN1987

UN proper shipping name ALCOHOLS SOLUTION, N.O.S. (2-PROPANOL)

Transport hazard class(es) 3
Subsidary class(es) Packaging group III
Environmental hazards No
ERG Code 3L

Special precautions for user

Other Information

Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY, Y203

IMDG

UN number UN1987

UN proper shipping name ALCOHOLS SOLUTION, N.O.S. (2-PROPANOL)

Transport hazard class(es) 3
Subsidary class(es) Packaging group III
Environmental hazards No
Marine pollutant
Labels required 3

EmS F-E, S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transportation in bulk according to Annex II of MARPOL 73/78 and IBC Code

Section 15 - Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

This substance/mixture is not intended to be transported in bulk.

TSCA Section 12(b) Export Notification (40 CFR707, Subpt. D) Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed

CERCLA Hazardous Substance List (40 CFR 302.4

Components Result 2-Butoxyethanol (CAS 111-76-2) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard CategoriesImmediate HazardYesDelayed HazardNoFire HazardYesPressure HazardNo

Reactivity Hazard No
SARA 302 Extremely hazardous substance Not listed.
SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

 Chemical name
 CAS #
 % by wt.

 2-Butoxyethanol
 111-76-2
 10 - 15

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HSPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.
Food and Drug Administration (FDA) Not regulated.

US state regulations

US.Massachusetts RTK - Substance List Components

2-Propanol (CAS 67-63-0) 2-Butoxyethanol (CAS 111-76-2) 2-Amino Ethanol (CAS 141-43-5)

US.New Jersey Worker and Community Right-to-Know Act Components

2-Propanol (CAS 67-63-0) 2-Butoxyethanol (CAS 111-76-2) 2-Amino Ethanol (CAS 141-43-5)

US.Pennsylvania RTK - Hazardous Substances

Components

2-Propanol (CAS 67-63-0) 2-Butoxyethanol (CAS 111-76-2) 2-Amino Ethanol (CAS 141-43-5)

US.Rhode Island RTK

Components

2-Butoxyethanol (CAS 111-76-2) 2-Amino Ethanol (CAS 141-43-5)

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to expose you to any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory Name	On Inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notifed Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes
Unites States Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Section 16 - Other information, including date of preparation or last version

Revision date 1/17/2021

Version # 01

HMIS Hazard Codes

Disclaimer

Health 2 Flammability

Physical Hazard

0

PPE

The information contained herein was obtained from current and reliable sources. However, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions for use, handling, storage and disposal of this product are beyond the manufacturer's control, it is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense arising from the product's improper use. No warranty, expressed or implied, regarding the product described herein shall be created by or inferred from any statement or omission in this SDS. Various government agencies may have specific regulations concerning the transportation, handling, storage, use or disposal of this product which may not be reflected in this SDS. The user should review these regulations to ensure full compliance.

^{*}A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).