BARE BONES® Low Odor

Low Odor All-Purpose Speed Stripper

DESCRIPTION

BARE BONES® LOW ODOR is a superior floor stripping formula that can be used anywhere, anytime! Like the original BARE BONES that set the standard for performance and labor savings some 20 years ago, BARE BONES® LOW ODOR from NCL provides the same rapid penetration and complete removal of even heavily burnished floor finish in a low odor formula that can be used in hospitals, schools and universities and office buildings. NCL chemists have designed a wetting system that keeps BARE BONES® LOW ODOR working at maximum effectiveness, with powerful film removing action easily cuts through multiple layers of finish easily! BARE BONES® LOW ODOR is a must for all professional floor care systems.

PRODUCT FEATURES / BENEFITS

- Low odor
- No scrubbing machine needed
- High use-dilution for greater economy

DIRECTIONS FOR USE

Dilute BARE BONES® Low Odor following dilution

ecommendations below. Dilute using cold or mildly warm water only.

Light/Normal Buildup:

8 oz per gallon of water (1:16)

Heavy Buildup (Burnished): 20 oz per gallon of water (1:5) Mop/Wet Vacuum Stripping System: Apply liberally with a mop to an area small enough so as not to allow the product to dry and allow to stand for 3 to 5 minutes. Agitate with a mop and remove solution and old finish with a wet vacuum. Allow floor to dry thoroughly and apply new finish as directed by manufacturer. If complete stripping is not accomplished repeat the above

SPECIFICATIONS

Color	Clear
Odor	Mild
рН	11.7 ± 0.3
pH (1:5)	11.2 ± 0.3
pH (1:16)	10.9 ± 0.3
Flash Point	> 212.0 °F (> 100.0 °C)
Upper Cloud Point	> 130°F
Lower Cloud Point	< 33°F
Viscosity (cps)	< 5

SAFETY INFORMATION

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF. SWALLOWED, IN CONTACT WITH SKIN OR IF INHALED. MAY CAUSE RESPIRATORY

IRRITATION. KEEP OUT OF THE REACH OF CHILDREN **Precautionary statement:**

Prevention:

Do not breathe mist or vapor. Use only in well-ventilated areas. Wear protective gloves/clothing and eye/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Keep out of reach of children

Response:

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse



Stripper



- Cuts through multi-layers of finish easily.
- Superior wetting.

procedure before re-application of recommended NCL Floor Finish.

Floor Machine Stripping System: Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply recommended NCL Floor Finish as per instructions.

Note: Asphalt tile, Linoleum, and other sensitive floor surfaces may be damaged by contact with stripping solution. We recommend that a spot test be conducted before general use.

Water Solubility	Complete
Finish Removal	Excellent
Damage to Resilient Tiles	Minimal
Density (lbs/gal)	8.15 ± 0.1
Specific Gravity (g/cc)	0.98 ± 0.01
Free Rinsing	Yes
Low Foaming	Yes
Shelf Life 1 year minimum in original unopened container	

skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/ doctor. Wash contaminated clothing before reuse.

Storage:

Store locked up. Store in a well-ventilated place. Keep cool. **Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional safety measures: Read the entire label and SDS before using this product, and for additional first aid measures. SDS for this product is available on the web at www.nclonline.com



1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517 www.nclonline.com • e-mail:info@nclonline.com



