



ENDURA™

Ultra Premium Water-Based Urethane Wood Finish

DESCRIPTION

Superior resistance to wear, scuffing, black marking, and soil. Single component formula simplifies application and means no mixing and no pot life, yet rivals 2-part finish systems for overall performance! VOC compliant. Reduces down time associated with traditional solvent-based wood floor products; floors are ready for foot traffic in 24 hours. Designed for all types of wood floors; dries crystal clear.

PRODUCT FEATURES / BENEFITS

- Superior resistance to wear, scuffing
- Requires no mixing
- Black Heel Mark Resistant
- VOC Compliant
- Dries Crystal Clear
- Reduces wood floor down time

DIRECTIONS FOR USE

Apply ENDURA™ Wood Floor Finish using a T-bar and approved wood floor application pad. ENDURA™ is ready for application—it requires no mixing. Do not apply this product to bare, unsealed wood floors. Read all label instructions prior to applying this product.

FINISH APPLICATION PROCEDURES:

Mix ENDURA™ before initial use by rolling the container gently on the floor. Avoid creating foam in the container. Allow foam to dissipate before beginning application. Apply at a rate of 700-800 square feet per gallon. Apply ENDURA™ using a T-bar applicator with new, clean applicator pad in a thin, even coat going with the grain of the wood. Adequate ventilation must be maintained for coating and drying.

1. Ensure the floor surface is properly prepared for finish application. The floor surface should be clean, dry and free of any dust.
2. Pour a 4" wide line of ENDURA™ along the starting wall.
3. Holding the applicator at a snow plow angle (45°), walk at a slow, even pace maintaining a wet edge at all times and moving the finish to the opposite wall. Overlap passes by 3" to 4". Walking too fast can produce foaming in the finish and result in air bubbles trapped in the finish.
4. At the end of each run, turn the applicator toward you and pad out the applicator parallel to the wet edge. Feather out all turns; if pushed too hard or too fast, drips will fly off the applicator. Missed areas can be touched up if seen right away.
5. Allow the finish to dry thoroughly, at least 6 hours (longer in humid conditions).
6. Additional coats of ENDURA™ can be applied in a window of 6 - 12 hours. After 12 hours follow ROUGHING PROCEDURES to ensure proper adhesion between coats.

ROUGHING PROCEDURES:

If additional coats of ENDURA™ are to be applied 12 hours or more after the previous application, roughing the floor surface will ensure proper adhesion between coats.

DRY PROCESS

1. Roughen floor surface using a 175 rpm swing machine with a maroon floor pad or 120 grit screen. Use overlapping passes until floor surface is roughened evenly.
2. Vacuum all surfaces thoroughly to remove dust in and around the work area.
3. Tack the floor surface using FAST BREAK™ Routine Wood Cleaner following the Routine Cleaning / Tacking instructions on the FAST BREAK™ product label.
4. Follow FINISH APPLICATION PROCEDURES.


WET PROCESS

1. Roughen the floor surface using PIVOT™ Intensive Prep Wood Cleaner following the Wet Screening instructions on the PIVOT™ product label.
2. Tack the floor surface using FAST BREAK™ Routine Wood Cleaner following the Routine Cleaning / Tacking instructions on the FAST BREAK™ product label.
3. Follow FINISH APPLICATION PROCEDURES.

SCRUBBING & RECOATING:

As the floor surfaces age, they become dirty and scuffed. It can benefit from a good cleaning and application of a fresh coat of ENDURA™.

1. Dust mop floor surface. Remove chewing gum and other sticky materials with a putty knife.
2. Clean floor surface thoroughly with PIVOT™ Intensive Prep Wood Cleaner following the Deep Cleaning prior to Recoating instructions on the PIVOT™



product label.

3. Follow ROUGHING PROCEDURES and FINISH APPLICATION PROCEDURES.

NOTE: Floors that have been previously coated should be tested in an inconspicuous area before recoating to determine compatibility of ENDURA™ with the existing finish.

DAILY MAINTENANCE:

Keeping wood floor surfaces clean, free of dust and dirt is essential to cleanliness and proper surface maintenance.

1. Dust mop wood floors a minimum of once per day (more often if required), using dust mops treated with MID-COURT™ Water-Based Dust Mop Treatment.
2. Spot clean spills, salt residue, etc. with FAST BREAK™ Wood Cleaner & Maintainer. Follow the Spot cleaning with towels instructions on the FAST BREAK™ label.

ROUTINE MAINTENANCE:

1. Clean the floor surface routinely with FAST BREAK™ Routine Wood Cleaner following the Routine Cleaning / Tacking instructions on the FAST BREAK™ product label.

INTERIM MAINTENANCE:

1. Autoscrub the floor surface using FAST BREAK™ Routine Wood Cleaner following the Interim Cleaning Process instructions on the FAST BREAK™ product label.

SPECIFICATIONS

Type.....	Polyurethane
Total Solids (%).....	30.0 ± 1.0
pH.....	8.0 ± 0.5
Coverage (sq. ft./gal).....	600-800
Drying Time (minutes).....	60
Color.....	White, opaque liquid
Odor.....	Mild Characteristic
Film Appearance.....	Crystal Clear
Specific Gravity (g/cc).....	1.04 ± 0.01
VOC content (g/l).....	270
MFMA Approved.....	Yes
Slip Resistant (UL Certified).....	Yes
Shelf Life.....	1 year minimum in original unopened container

SAFETY INFORMATION

WARNING: SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. KEEP OUT OF REACH OF CHILDREN.



Precautionary statement

Prevention: Do not breathe the mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection.

Response: Wash thoroughly after handling. If exposed or concerned: Get medical advice/attention.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local authority requirements.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only



Floor Coating and F
As to Slip Res
18E



World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com