



Labor Saving Sealer / Finish

DESCRIPTION

ONE represents a true advance in floor finish performance. This super high solids formula produces unmatched "off-the-mop" gloss with extended gloss retention. Utilizing exclusive Advanced Polymer Technology, this superior floor coating will produce maximum gloss with fewer coats than conventional floor finishes. Combination sealer / finish saves product costs. Exceptional response to UHS burnishing.

PRODUCT FEATURES / BENEFITS

- Applicable for use in high traffic areas / Achieves maximum versatility
- MPS77 Advanced Polymer Technology produces exceptional gloss from fewer coats
- Sealer/finish combination for product cost savings
- Maximum resistance to scratches and scuffs

DIRECTIONS FOR USE

Floor Preparation: Using BARE BONES®, No-rinse, No-scrub Liquifying Stripper, strip off old finish and wax following product label directions. For baseboards and corners, use PIZAZZ Baseboard Stripper. Make sure the floor is clean and dry before applying finish.

Application: Using a clean mop or applicator apply a thin uniform coat of ONE. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period.

High Speed Buffing and Burnishing: This is an ideal product for use with high speed polishing or burnishing machines of

1500- 3000 rpm (electric, battery or propane). Dust mop using CONTROL Dust Mop Treatment prior to high speed buffing or burnishing. Buff or dry burnish using an aggressive natural hair burnishing pad. For spray buffing, mop-on restoration or auto scrubbing use SPIT-SHINE™ Ultra High Speed Kleen & Burnish.

Maintenance: Dust mopping daily using mop treated with CONTROL Dust Mop Treatment. Use a recommended NCL neutral floor cleaner for routine cleaning. Spray buffing to remove embedded soils is recommended using SPIT-SHINE Kleen & Burnish. Worn areas, or the entire floor, may be scrubbed and recoated as required to maintain a uniform high gloss.

SPECIFICATIONS

Type Pure acrylic polymers
 pH 8.3 ± 0.3
 Coverage (sq. ft./gal)..... 3,000
 Drying Time (minutes) 30
 Color White, opaque liquid

Odor Typical acrylic
 Film Appearance Clear
 Powdering None
 Flash Point None
 Slip Resistant Yes
 Shelf Life 1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.


This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING

For Commercial and Industrial Use Only



FLOOR CARE



CLASSIFIED Floor Coating and Finishing Material
As to Slip Resistance Only
18EL



World Class Cleaning Solutions®

401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com