



World Class Cleaning & Hygiene Solutions®

- Enhances Floor Appearance
- Produces Durable Coating
- Protects Floor Surfaces
- For LVT, Linoleum & More

Education



Retail



Restaurants



Hospitality



Next Century™

LVT / Linoleum High Gloss Floor Coating



Next Century™

LVT / Linoleum High Gloss Floor Coating

Product #2623

DESCRIPTION

Use NCL® NEXT CENTURY™ LVT / Linoleum High Gloss Floor Coating to provide a maintainable "wear layer" to improve cleaning efficiency, and protect your flooring investment. This advanced product creates a protective barrier that adds a high gloss shine to reveal the true character, color and beauty of the floor. This water-resistant coating improves slip resistance and improves the cleaning ability on the surface. NEXT CENTURY™ is recommended for use on LVT & Linoleum floors; use it on new flooring to protect and enhance the original beauty and look. Use it on worn flooring to restore and revitalize the look of the surface.

PRODUCT FEATURES / BENEFITS

- Offers a high gloss to enhance appearance of floor surface
- Produces a durable coating for added ease-of-maintenance
- Protects surface to add years of service to floor substrate
- Use for LVT, Linoleum and other hard surfaces

DIRECTIONS FOR USE

APPLICATION PROCEDURES:

Using a clean mop or applicator apply thin uniform coats of NEXT CENTURY™ LVT / Linoleum Floor Coating. Allow to dry for a minimum of 20 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

ROUTINE MAINTENANCE PROCEDURES:

Sweep large debris and dust mop. Damp mop or clean with an automatic scrubber using your appropriate floor pad and NCL LVT CLEAN™ following label directions.

SCRUB AND RECOAT PROCEDURES:

1. Dust mop floor to remove all dry soil and loose debris prior to cleaning.
2. Clean the surface using NCL® SURFACE PREP™ at a dilution ratio of 1:6 to 1:10, depending on build-up, using a mop and bucket or automatic scrubber and appropriate floor cleaning pad. Rinse and allow to dry thoroughly.
3. Using a wet mop or microfiber applicator, apply NEXT CENTURY™ at a rate of 2500 sq. ft. per gallon. Allow to dry thoroughly.
4. Worn, dull, lifeless floors may require more than one application. Repeat step 3 as desired, being sure to allow adequate time for drying between each coat.
5. Routine cleaning is recommended using NCL LVT-CLEAN™ to prolong the life of the coating and LVT.

SPECIFICATIONS

Type	Acrylic
pH	8.2 ± 0.2
Drying time (minutes)	20
Color	White, opaque
Film	Clear, non-yellowing
Freeze thaw stable	Yes
Flash Point	None
Powdering	Nil
Detergent Resistant	Yes (after 24 hr.)
Leveling	Superior
Recoatability	Excellent
Removability	Excellent
Durability	Superior
Soil Resistance	Superior
Scuff Resistance	Superior
Black Mark Resistance	Superior
Deep Gloss Appearance	Superior
Slip Resistance	Excellent
Buffing Response	Excellent
Shelf Life	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING - For Commercial and Industrial Use Only



FLOOR CARE

Product	Code #	Packaging	Weight	Cube	Units per Pallet (Layers/Total Cases)
Next Century™ LVT / Linoleum High Gloss Floor Coating	2623	4 x 1 Gallons	37 lbs.	1.13	12/60

Available only through your NCL Authorized Local Independent Distribution Partner



World Class Cleaning & Hygiene Solutions®

401 N. 10th Street • Philadelphia, PA 19123 USA
 1-800-NAT-CHEM • 215-922-1200 • Fax: 215-922-5517
www.nclonline.com • sales@nclonline.com